

DUVILAX® BSS-3/40

Chemical industry
Rubber-making chemicals manufacture
Household chemicals

Composition:

A homopolymer polyvinyl acetate dispersive containing filling and softening agents and other additives. The emulsion system is composed of a non-ionic and polyvinyl alcohol acting as protective colloid. Duvilax® BSS - 3/40 does not pose any health or usage risks (no R-sentences and S-sentences).

Properties:

A water dispersion of white color with a characteristic smell. It is non-toxic, incombustible, non-explosive, posing no health or hygienic hazards and biodegradable. The dispersion film is transparent, soft, flexible and non-adhesive.

Parameters:

Dry matter content	min. 40.0%
Viscosity	600- 900 mPa.s (Rheotest) 1 300-2 500 mPa.s (according to ISO 2555, Brookfield RVT)
pH value	5 - 7
min. film-forming temperature	14°C

Usage:

Duvilax® BSS-3/40 is a special dispersed joint used to produce granule materials in chemical industry. In household chemicals it is used as a synthetic substance for stiffening linen, household linen, working clothes and other textile products, where is needed high hardness, lifespan and antistatic efficacy.

Packing:

Packed in 30 kg PE -kegs; 125 kg PE- barrels; 200 kg steel barrels; 1000 kg plastic container, road tank cars and railway tanks.

Storage:

Duvilax® BSS - 3/40 is stored in original, undamaged, closed packaging at temperatures from 5°C to 40°C and must not be exposed to direct sunshine. Goods delivered in tanks is stored in special storage bins protected against corrosion caused by mildly acid medium. There must not be free airflow from the surroundings in bins (for instance use water valve) or there must be mixer given. It is necessary to mind not to mix it with other medias and also with microbiological exceptionable materials. After emptying the tank it is necessary to clean and disinfect with the help of biocide agent.

Guarantee period:

6 months under the observation of storage conditions.

The given data are only of an informative character and are not complete. Before each use it is recommended to try an adhesive in concrete conditions. Further information can be obtained at:

0026



Producer:

Duslo, a. s.
Administratívna budova ev. č. 1236
927 03 Šafa
Slovenská republika

Sales contact:

Duslo, a. s.
Administratívna budova ev. č. 1236
927 03 Šafa
Slovenská republika

Tel.: +421 31 775 3388, 775 4391
Fax: +421 31 775 3018, 775 3078
E-mail: duvilax@duslo.sk
Internet: <http://www.duslo.sk/>
<http://www.duvilax.sk>