

DUVILAX® LS-50

INTERIOR WOOD ADHESIVE

Woodworking industry
Furniture industry

Composition:

An adhesive Duvilax® LS-50 is made on the basis of polyvinyl acetate dispersion in water. It does not prove any health or usage risks (no R-sentences and S-sentences).

Properties:

A water white- colored dispersion with a characteristic smell. It is non-toxic, incombustible, non-explosive, posing no health or hygienic hazards and biodegradable. The adhesive film is transparent, relatively hard, brittle and non- adhesive.

Usage:

Duvilax® LS-50 is a standard wood adhesive for interiors. It is used for assembly sticking in furniture manufacture, sticking of massive wood- peg joints, simple barb, ping, on mow, on pen-mortise etc. Glued object may be further working after 24 hours from gluing. It is also suitable for sticking paper, cardboard, textiles, cork and other absorptive materials mutually. Its consistency should be original and it must not be diluted or otherwise treated.

Parameters:

Dry matter content	min. 48.0 %
Viscosity	3 000 – 6 500 mPa.s (Rheotest) 6 000 – 25 000 mPa.s (according to ISO 2555, Brookfield RVT)
pH value	4 – 6
min. film-forming temperature	12°C
open period	max.5 minutes
joint rigidity in shear (beech-beech)	min. 10 MPa
group of stress EN 204	D2

Fixing conditions:

Working temperature	min.15°C, in heating fixing max.100°C
Dampness of fixed particles	8-12%
Adhesive consumption (recommended)	120-200 g/m ²
Way of application	brush, roller, spatula, nozzle
Press power	min. 0.7 MPa
Press working time	20-40 min. according to type of joint and fixing conditions drying time at 20°C cca.24 hours (it means time of reached hardness adequate for further working)

Packing:

Packed in 1 kg, 3 kg, 5 kg and 10 kg buckets, 30 kg PE -kegs; 125 kg PE- barrels; 200 kg steel barrels; 1000 kg plastic container.

Storage:

Duvilax® LS-50 is stored in original, undamaged, closed packaging by temperatures from 5°C to 40°C and must not be exposed to direct sunshine.

Guarantee period:

The guaranteed period for the product delivered in packing up to 15 kg gross is 12 month. For the rest of the products it is 6 months, in the case of keeping the storage conditions mentioned above.

The given data are only of an informative character and are not complete. Before each use it is recommended to try an adhesive in concrete conditions. Further information can be obtained at:

0026



Producer:
Duslo, a. s.
Administratívna budova ev. č. 1236
927 03 Šafa
Slovenská republika

Sales contact:
Duslo, a. s.
Administratívna budova ev. č. 1236
927 03 Šafa
Slovenská republika

Tel.: +421 31 775 3388, 775 4391
Fax: +421 31 775 3018, 775 3078
E-mail: duvilax@duslo.sk
Internet: <http://www.duslo.sk/>
<http://www.duvilax.sk>