

# DUVILAX® LP

Building industry

## Composition:

A special adhesive is made on the basis of polyvinyl acetate dispersion. It is modified with filling agents, biocide and other additives. It does not pose any health or usage risks (no R-sentences and S-sentences).

## Properties:

A water cream- colored dispersion with a characteristic smell. It is non-toxic, incombustible, non-explosive, posing no health or hygienic hazards and biodegradable. After drying it makes continuous film that is cream- colored.

## Usage:

Duvilax® LP is a special dispersed adhesive used for sticking of unvarnished mosaic and lamellar parquetry from hard wood (except from beech), unvarnished cork floor coverings and cork wall tiles on the absorptive ground (i.e. concrete leveling layers). Its consistency should be original and it must not be diluted or otherwise treated.

## Parameters:

|                               |  |
|-------------------------------|--|
| Dry matter content            | min. 60.0 %  |
| Viscosity                     | 5 000 – 10 000 mPa.s (Rheotest)<br>15 000 – 25 000 mPa.s (according to ISO 2555, Brookfield RVT) |
| pH value                      | 4 – 6  |
| min. film-forming temperature | 12 °C  |
| open period                   | 5 - 15 minutes   |

## Fixing conditions:

|                      |                              |
|----------------------|------------------------------|
| Working temperature  | min. 15 °C                   |
| Relative humidity    | 40 - 75%                     |
| Ground plainness     | ±2 mm/2 m                    |
| Ground humidity      | max. 2 %                     |
| Adhesive consumption | 800 - 1 000 g/m <sup>2</sup> |
| drying time at 20°C  | min. 48 hours                |

## Packing:

Packed in 5 kg and 13 kg buckets, 30 kg PE -kegs; 125 kg PE- barrels; 200 kg steel barrels; 1000 kg plastic container.

## Storage:

Duvilax® LP is stored in original, undamaged, closed packaging by temperatures from 5°C to 40°C and must not be exposed to direct sunshine.

## Guarantee period:

The guaranteed period for the product delivered in packing up to 15 kg gross is 12 month. For the rest of the products it is 6 months, in the case of keeping the storage conditions mentioned above.

The given data are only of an informative character and are not complete. Before each use it is recommended to try an adhesive in concrete conditions. Further information can be obtained at:

0026



## Producer:

Duslo, a. s.  
Administratívna budova ev. č. 1236  
927 03 Šafa  
Slovenská republika

## Sales contact:

Duslo, a. s.  
Administratívna budova ev. č. 1236  
927 03 Šafa  
Slovenská republika

Tel.: +421 31 775 3388, 775 4391  
Fax: +421 31 775 3018, 775 3078  
E-mail: [duvilax@duslo.sk](mailto:duvilax@duslo.sk)  
Internet: <http://www.duslo.sk/>  
<http://www.duvilax.sk>