

DUVILAX® KA-31

VERTICAL PENETRATION

Building industry

Composition:

A copolymer on the base of vinyl acetate – acrylate in water environment. It does not contain any external softeners and filling agents. The emulsion system is composed of a non- ionogenous and an anionactive emulsifier. It does not prove any health or usage risks (no R-sentences and S-sentences).

Properties:

A water white- bluish colored dispersion with a characteristic smell. It is non-toxic, incombustible, posing no health or hygienic hazards and biodegradable. The dispersion film is transparent, extremely soft and non- adhesive.

Parameters:

Dry matter content	(16±1) %
Viscosity	5 – 50 mPa.s (Rheotest)
	5 – 80 mPa.s (according to ISO 2555, Brookfield RVT)
pH value	4 – 6
min. film-forming temperature	5°C

Usage:

Duvilax® KA - 31 Vertical penetration is a special solution used for letting in of ground that is made of plaster and plaster cardboard. Then it is used for adjustment of porous or strongly sucked ground (cement spawn, new concrete and suchlike). On such an adjusted ground is put thin or whole spawn, spatula, painting or before gluing tiles and paving. Deep penetration is recommended for deep hardening of sucking surfaces and for their dustless adjustment. It is suitable for interiors, protected exteriors and for floor heating.

Packing:

Packed in 1kg, 3 kg, 5 kg and 10 kg bucket, 30 kg PE -kegs; 125 kg PE- barrels; 200 kg steel barrels; 1000 kg plastic container.

Storage:

Duvilax® KA - 31 Vertical penetration is stored in original, undamaged, closed packaging by temperature from 5°C to 40°C and must not be exposed to direct sunshine.

Guarantee period:

The guaranteed period for the product delivered in packing up to 15 kg gross is 12 month. For the rest of the products it is 6 months, in the case of keeping the storage conditions mentioned above.

The given data are only of an informative character and are not complete. Before each use it is recommended to try an adhesive in concrete conditions. Further information can be obtained at:

0026



Producer:

Duslo, a. s.
Administratívna budova ev. č. 1236
927 03 Šafa
Slovenská republika

Sales contact:

Duslo, a. s.
Administratívna budova ev. č. 1236
927 03 Šafa
Slovenská republika

Tel.: +421 31 775 3388, 775 4391
Fax: +421 31 775 3018, 775 3078
E-mail: duvilax@duslo.sk
Internet: <http://www.duslo.sk/>
<http://www.duvilax.sk>