

DUVILAX® L-58

Building industry

Composition:

Duvilax® L-58 is an adhesive made on the basis of copolymer dispersion. It is modified with filling agents, biocide and other additives. It does not pose any health or usage risks (no R-sentences and S-sentences).

Properties:

A water dispersion of grey-yellowish to light brown color with a characteristic smell. It is non-toxic, incombustible, non-explosive, posing no health or hygienic hazards and biodegradable. After drying it makes continuous film that is light brown colored.

Usage:

Duvilax® L-58 is a universal building adhesive. It is used for sticking textile and PVC floor coverings, linoleum, marmolea, vinyl-asbestos and marble paving tiles, ceramic and polystyrene wall tiles etc. These materials can be stuck on concrete, wood fibre and wood chip board foundations as well as on anhydrate and plaster leveling layers. Ceramic products can be fixed to non-absorptive materials, too. It is used non-diluted. To lower liquidity possible increase thickness of adhesive cement and/or soft sand can be mixed before gluing. Spatula is used for layering.

Parameters:

Dry matter content	min. 58.0 %
Viscosity	3 000 – 6 000 mPa.s (Rheotest) 13 000 – 25 000 mPa.s (according to ISO 2555, Brookfield RVT)
pH value	4 – 6
min. film-forming temperature	8°C
open period	2 - 6 minutes (depend on absorption of ground)

Fixing conditions:

Working temperature	min. 15°C
Relative humidity	40 - 75%
Ground plainness	±1 mm/2 m
Ground humidity	max. 4 %
Adhesive consumption	350 - 500 g/m ²
drying time at 20°C	min. 1 hour

Packing:

Packed in 1 kg, 3 kg, 5 kg and 10 kg buckets, 30 kg PE -kegs; 125 kg PE- barrels; 200 kg steel barrels; 1000 kg plastic container.

Storage:

Duvilax® L-58 is stored in original, undamaged, closed packaging by temperatures from 5°C to 40°C and must not be exposed to direct sunshine.

Guarantee period:

The guaranteed period for the product delivered in packing up to 15 kg gross is 12 month. For the rest of the products it is 6 months, in the case of keeping the storage conditions mentioned above.

The given data are only of an informative character and are not complete. Before each use it is recommended to try an adhesive in concrete conditions. Further information can be obtained at:

0026



Producer:

Duslo, a. s.
Administratívna budova ev. č. 1236
927 03 Šafa
Slovenská republika

Sales contact:

Duslo, a. s.
Administratívna budova ev. č. 1236
927 03 Šafa
Slovenská republika

Tel.: +421 31 775 3388, 775 4391
Fax: +421 31 775 3018, 775 3078
E-mail: duvilax@duslo.sk
Internet: <http://www.duslo.sk/>
<http://www.duvilax.sk>